

NON RETURN VALVES



MADE IN ITALY

NON RETURN VALVES

Working pressure 16 bar

Working temperature with NBR rubber seal -10 +80°C


Working temperature with VITON rubber seal -10 +200°C

Valve body EN 12164:98 CW 614N


Spring EN 10270-3

Upon request some items are also available with " F " size in FEMALE version

Item	F	F1	A	D	H	L
BX16VR102	3/8 F	3/8 M	1/8	9	38	51
BX16VR105	1/2 F	3/8 M	1/8	9	40	53
BX16VR114	1/2 F	1/2 M	1/8	11	43	57
BX16VR118	3/4 F	1/2 M	1/8	11	48	58
BX16VR120	3/4 F	3/4 M	1/8	16	58	74
BX16VR123	1" F	1" M	1/8	20	68	89



Item	F	F1	A	D	H	L
BX16VR185	1/4 M	3/8 M	1/8	6	43	42
BX16VR132	3/8 M	3/8 M	1/8	9	41	47
BX16VR108	1/2 M	3/8 M	1/8	9	44	51
BX16VR113	1/2 M	1/2 M	1/8	11	48	56
BX16VR117	3/4 M	1/2 M	1/8	11	48	57
BX16VR179	3/4 M	3/4 M	1/8	16	61	75
BX16VR121	1" M	3/4 M	1/8	16	58	74



Item	F	F1	A	D	D1	H	L
BX16VR101	1/4 M	3/8 M	1/8	6	10	43	41
BX16VR138	3/8 M	3/8 M	1/8	9	10	41	46
BX16VR133	3/8 M	3/8 M	1/8	9	12	41	46
BX16VR110	1/2 M	3/8 M	1/8	9	10	44	49
BX16VR111	1/2 M	3/8 M	1/8	9	12	44	49
BX16VR127	1/2 M	1/2 M	1/8	11	14	48	53
BX16VR115	1/2 M	22X1,5 M	1/8	11	15	48	53
BX16VR116	3/4 M	3/8 M	1/8	9	10	47	51
BX16VR136	3/4 M	1/2 M	1/8	11	14	48	52
BX16VR119	3/4 M	22X1,5 M	1/8	11	15	48	52
BX16VR181	3/4 M	3/4 M	1/8	16	18	61	71

