


2090


RIDUZIONE CILINDRICA - REDUCER (PARALLEL)



Codice Code	A	A1	B	L	CH	Conf. Pack.
0209000010WNT	1/8	M5	6	10.5	14	50
0209000015WNT	1/4	1/8	8	13	17	50
0209000019WNT	3/8	1/8	9	14	19	25
020900001ADNT	1/2	1/8	10	15.5	24	25
020900001AANT	3/8	1/4	9	14	19	25
020900001AENT	1/2	1/4	10	15.5	24	25
020900001AFNT	1/2	3/8	10	15.5	24	25
020900001EDNT	3/4	1/4	12	17.5	30	25
020900001ALNT	3/4	3/8	12	17.5	30	25
020900001AMNT	3/4	1/2	12	17.5	30	25

2092


RIDUZIONE CILINDRICA CON O-RING NBR - REDUCER (PARALLEL) WITH NBR O-RING



Codice Code	A	A1	B	L	CH	Conf. Pack.
0209200001	1/8	M5	5,4	9,4	13	50
0209200002	1/4	1/8	5,5	11,1	16	50
0209200003	3/8	1/8	6,5	12,6	20	25
0209200004	3/8	1/4	6,5	12,6	20	25
0209200005	1/2	1/4	9,6	14,6	25	25
0209200006	1/2	3/8	9,6	14,6	25	25
0209200007	3/4	1/2	11,1	16	34	25
Temperatura minima / Minimum temperature:						-20 °C
Temperatura massima / Maximum temperature:						+80 °C

2095


RIDUZIONE CILINDRICA - REDUCER (PARALLEL)



ARTICOLO NON NICHELATO ARTICLE NOT NICHEL-PLATED				
Codice Code	A	A1	L	Conf. Pack.
0209500015W00	1/4	1/8	8	50
020950001AA00	3/8	1/4	9	50
020950001AF00	1/2	3/8	10	50
020950001AM00	3/4	1/2	14	25
020950001AQ00	1"	3/4	20	25

2096


GHIERA - NUT



Codice Code	A	L	CH	Conf. Pack.
02096000102NB	1/8	4.5	14	50
02096000103NB	1/4	5	17	50
02096000104NB	3/8	6	20	50
02096000105NB	1/2	6	24	50

2110

NIPPLO CONICO ORIENTABILE - ORIENTING NIPPLE (TAPER)



Codice Code	A	B	CH1	CH2	L	Conf. Pack.
0211000001	1/8	7.5	13	13	25	50
0211000002	1/4	11	16	15	33	25
0211000003	3/8	11.5	20	17	35.5	25
Temperatura minima / Minimum temperature:						-20 °C
Temperatura massima / Maximum temperature:						+80 °C
Pressione minima / Minimum pressure:						-0.99 bar (-0.099 MPa)
Pressione massima / Maximum pressure:						+15 bar (1.5 MPa)