


82242

ADATTATORE FEMMINA NPTF - MASCHIO CILINDRICO


- ADAPTER FEMALE NPTF - MALE G THREAD



Codice Code	A	B	H	L	CH	Conf. Pack.
8224200012WNB	1/8	1/8	6	17	14	25
8224200016WNB	1/4	1/4	8	23	17	25
822420001ABNB	3/8	3/8	9	24	22	25
822420001AGNB	1/2	1/2	12	31.5	27	25

7000

SILENZIATORE - SILENCER



dB = Livello di rumore in (dB) a 6 bar
Noise level in (dB) at 6 bar


CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTICS

Pressione massima /	maximum pressure:	10 bar
Temperatura minima /	minimum temperature:	-10°C
Temperatura massima /	maximum temperature:	+80°C
Soglia di filtrazione /	filtration threshold:	50 µm

Codice Code	A	F	B	H	dB	Conf. Pack.
0700000001	1/8	4.5	12.5	21	81	25
0700000002	1/4	6	15	25	83	25
0700000003	3/8	8.5	19	34.5	87	25
0700000004	1/2	8	23	43	90	25
0700000005	3/4	9	30	50	92 a 4 Bar	25
0700000006	1"	11	37	60.5	92 a 4 Bar	10

7010

SILENZIATORE - SILENCER



dB = Livello di rumore in (dB) a 6 bar
Noise level in (dB) at 6 bar


CARATTERISTICHE TECNICHE / TECHNICAL CHARACTERISTICS

Pressione massima /	maximum pressure:	12 bar
Temperatura minima /	minimum temperature:	-10°C
Temperatura massima /	maximum temperature:	+80°C
Soglia di filtrazione /	filtration threshold:	100 µm

Codice Code	A	F	H	CH	dB	Conf. Pack.
0701000001	1/8	6	14	13	73	25
0701000002	1/4	7	17	16	74	25
0701000003	3/8	8	18	19	85	25
0701000004	1/2	10	20	24	89	25
0701000005	3/4	10	23	30	90	25

7020

SILENZIATORE CON RETE IN FILO DI ACCIAIO INOX 304
SILENCER WITH WIRE MESH STAINLESS STEEL 304



dB = Livello di rumore in (dB) a 6 bar
Noise level in (dB) at 6 bar

CARATTERISTICHE TECNICHE / Technical characteristics

Pressione massima /	maximum pressure:	12 bar
Temperatura minima /	minimum temperature:	-10°C
Temperatura massima /	maximum temperature:	+80°C
Soglia di filtrazione /	filtration threshold:	100 µm

Codice Code	A	F	H	CH	dB	Conf. Pack.
0702000001	M5	4	9	8	-	25
0702000002	1/8	6	15	13	74	25
0702000003	1/4	7	18	16	72	25
0702000004	3/8	8	20	19	88	25
0702000005	1/2	10	22	24	90	25
0702000006	3/4	10	26	30	90	25
0702000007	1"	12	28	36	92	10